

# GROWATT THOR Smart EV Charger

THOR 07AS-S/P-V1(Single Phase)

- Compatible with all branded EV
- Integration in existing & new-installed PV system
- Charge EV with 100% renewable energy by surplus solar power
- APP smart control & smart scheduling
- IP65 design for indoor or outdoor use



**GROWATT**

[en.growatt.com](http://en.growatt.com)

P O W E R  
- I N G O  
T O M O -  
R R O W O



Datasheet	THOR 07AS-P-V1	THOR 07AS-S-V1
<b>Input &amp; output</b>		
Input voltage	230V AC	
Input frequency	50/60Hz	
Output voltage	230VAC	
Max. output power	7KW	7KW
Max. output current	32A	32A
Charging interface type	IEC 62196-2, Type 2	
Connection	Plug	Socket
Cable length	5m	/
<b>Protection</b>		
Over voltage protection	Yes	
Under voltage protection	Yes	
Over load protection	Yes	
Earth leakage protection	AC 30mA + DC 6mA	
Over-temp protection	Yes	
Lightning protection	Yes	
<b>Function and accessory</b>		
Ethernet/WIFI/4G	Yes/Yes/Opt	
LCD	No	
Charge activation	APP/Plug&Charge/RFID	APP/Plug&Charge/RFID
LED Indicator light	Yes	
Emergency stop button	Yes	
Multiple workmodes	Fast/ PV linkage/ off-peak/ load balancing	
Communication protocol	OCPP 1.6	
MID meter	Opt	
Installation	Floor/wall-mounting	
<b>General</b>		
Protection degree	IP65	
Environment temperature	-25°C ~ +50°C	
Relative humidity	5-95% non-condensing	
Maximum altitude	<2000m	
Cooling	Natural cooling	
Standby power consumption	<8W	
Dimension (W/H/D)	240/380/164mm	
Weight	3.5kg	5kg
Wall-mounting bracket/ Ground-mounting pole	Yes/Opt	
CE (LVD&EMC, EN 61851-1, EN 61851-22, EN 61000-6-3, EN 61000-6-1), IEC 62196		